

# HD 148 DEGREASER

Versatile, highly alkaline heavy duty degreaser



## BENEFITS

- Can be used in hot or cold water
- Suitable for use in all water conditions
- Fast and effective removal of grease and fat
- Free rinsing does not leave residues or product build-up

## DILUTION RATES

- **FOAM APPLICATION:** Ecosolve should be used at a concentration of 3 – 6% (30 – 60 ml per liter of water) at temperatures from ambient to 60°C through a pressure wash system fitted with a foam lance. Allow at least 5 minutes contact time before rinsing with high pressure.
- **MANUAL APPLICATION:** Apply at concentration of 1 – 3% (10- 30 ml per liter of water, scrub, allow at least 5 minutes contact time and rinse.
- **IMMERSION:** Use at 1 – 5%, allow to soak overnight

## APPLICATIONS & DIRECTIONS

- Apply to surface to be cleaned using a brush, sponge, mop, rag or hand-held sprayer. Some mechanical action is necessary before allowing at least 5 minutes contact time before rinsing.
- For Dip Applications, allow to soak for 30 minutes before rinsing.

## AREAS OF USAGE

- Heavy Industry.
- Light Industry
- Motor Workshops
- DIY Handymen

## TECHNICAL DATA

- APPEARANCE: Clear liquid
- ODOUR: Oxitol
- pH:12-13
- SHELF LIFE: 2 Years

## RELATED PRODUCTS

- ECOSOLVE
- ALUSHINE
- HAND GRIT

## HEALTH AND SAFETY

**Product in eyes:** Flush eyes with water holding eye-lids apart.

**Product on skin:** Rinse skin with cool running water, remove contaminated clothing and wash well before re-use.

**Product Ingested:** Rinse mouth at once, do not induce vomiting. Never give anything by mouth to an unconscious person.

**Product Inhaled:** Move person to fresh air, if breathing is difficult administer oxygen and seek medical attention



Management System  
ISO 9001:2015



www.tuv.com  
ID 9105086504