# TOUGHCOAT

High durability floor polymer dressing- 15% solids









# **BENEFITS**

- Contains a metal interlock, multi-coatable polymer which forms a clear, tough, long wearing shine.
- Recommended for use on floors made of linoleum, vinyl, rubber and unglazed ceramic floors



## **DILUTION RATES**

Use neat



### **APPLICATIONS & DIRECTIONS**

- Before use test this product on an inconspicuous are to ensure compatibility with the surface.
- Strip old finish from floor using FLOORSTRIP or AMMONIA STRIP, rinse completely and allow to air-dry.
- Apply in thin even coats using a lamb's wool applicator, alternate direction of consecutive coats
- Allow 30 minutes drying time between coats



#### **RELATED PRODUCTS**

- MOP and SHINE
- TOUGH GLOSS
- FLOOR STRIP
- **AMMONIA STRIP**



#### **HEALTH AND SAFETY**

Product on skin: Rinse skin with cool running water, remove contaminated clothing and wash well before re-use. Product Ingested: Rinse mouth at once, do not induce vomiting. Never give anything by mouth to an unconscious person. Product Inhaled: Move person to fresh air, if breathing is difficult administer oxygen and seek medical attention

Product in eyes: Flush eyes with water holding eye-lids apart.







### **AREAS OF USAGE**

- Shopping Malls
- Retail Stores
- Office Buildings
- Schools
- Hospitals



# **TECHNICAL DATA**

- APPEARANCE: White liquid
- ODOUR: Characteristic
- pH: 7-8 (100%)
- SHELF LIFE: 2 Years





Management System ISO 9001:2015



www.tuv.com ID 9105086504

Tel: +27 11 776 5076

- Cell: +27 83 469 3828
- emial: richard@bdchemicals.co.za
- 56 Stanley Rd, Knights P.O. Box 4120, Germiston South, 1411
- www.bdchemicals.co.za

QUALITY ASSURANCE: This product is manufactured in South Africa by BD Chemicals (Pty) Ltd under an ISO 9001 QUALITY MANAGEMENT SYSTEM, Certificate Number. 01 100 928474